



TECPO 1K Epoxy- Primer grau_EN

Version number: 1.0
Issued: 2026-07-11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

TECPO 1K Epoxy-Primer grau_EN

Article No.

300428

UFI code

331U-PUQC-H00S-EJYW

1.2. Relevant identified uses of the substance or mixture and uses advised against

Product type

PC9a - Coatings and paints, thinners, paint removers.

Relevant identified uses

adhesive primer

Application:

SU21 - Consumer uses: Private households (= general public = consumers).

SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen).

Process category:

PROC7 - Industrial spraying.

PROC11 - Non industrial spraying.

Not suitable for use in

No further relevant information available.



TECPO 1K Epoxy- Primer grau_EN

Version number: 1.0
Issued: 2026-07-11

1.3. Details of the supplier of the safety data sheet

Supplier

TECPO GmbH

Address

Dreherstraße 16-20

42899 Remscheid

Germany

Telephone

+49 2191 951 3305

Email

info@tecpo.de

Fax

+49 2191 951 33044

Web site

www.tecpo.de

Contact person

Baris Ünsal

1.4. Emergency telephone number

Poison center/Additional emergency number

+49 (0) 89 19240 (Available 24/7) - Poison Emergency Call Munich (Available for the public.)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Classification

Aerosol, Hazard category 1

Skin irritation, hazard category 2

Skin sensitisation, hazard category 1

Serious eye damage, hazard category 1

Specific Target Organ Toxicity — Single exposure, hazard category 3 - narcosis

Hazardous to the aquatic environment — Chronic hazard category 3

Hazard statements

H222, H229, H315, H317, H318, H336, H412

TECPO 1K Epoxy- Primer grau_EN

Description

The product is classified and labeled according to the CLP regulation.

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008

Hazard pictograms



Signal word

Danger

Hazard statements

H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.

Supplemental hazard statements

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P260 Do not breathe aerosol.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER/doctor.
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
P501 Dispose of contents/container to dispose of in accordance with local / regional / national / international regulations.

More information

Hazard-determining components of labeling:

Butan-1-ol
n-butyl acetate
Epoxy resin
acetone

TECPO 1K Epoxy- Primer grau_EN

2.3. Other hazards

Formation of explosive mixtures possible without adequate ventilation.

Other

This product does not contain any PBT or vPvB substances.

The product does not contain any substances with endocrine-disrupting properties.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical name	CAS No. EC No. REACH No. Index No.	Concentration	Classification	H-phrase M factor acute M factor chronic	Specific concentration limits ATE	Note
dimethyl ether	115-10-6 204-065-8 01-2119472128-37 603-019-00-8	25 - <50%	Flam. Gas 1, Press. Gas - Liquefied gas	H220, H280 - -		-
n-butyl acetate	123-86-4 204-658-1 01-2119485493-29 607-025-00-1	12,5 - <20%	Flam. Liq. 3, STOT SE 3 - narcosis	H226, H336, EUH066 - -		-
acetone	67-64-1 200-662-2 01-2119471330-49 606-001-00-8	12,5 - <20%	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3 - narcosis	H225, H319, H336, EUH066 - -		-
butan-1-ol	71-36-3 200-751-6 01-2119484630-38 603-004-00-6	5 - <10%	Flam. Liq. 3, Acute Tox. 4 - oral, Skin Irrit. 2, Eye Dam. 1, STOT SE 3 - resp. tract irrit., STOT SE 3 - narcosis	H226, H302, H315, H318, H335, H336 - -		-
Xylene (mixture of isomers)	- 905-588-0 01-2119488216-32 601-022-00-9	2,5 - <5%	Flam. Liq. 3, Asp. Tox. 1, Acute Tox. 4 - dermal, Skin Irrit. 2, Eye Irrit. 2, Acute Tox. 4 - inhalation, STOT SE 3 -	H226, H304, H312, H315, H319, H332, H335, H373 - -		-



TECPO 1K Epoxy- Primer grau_EN

Version number: 1.0
Issued: 2026-07-11

Chemical name	CAS No. EC No. REACH No. Index No.	Concentration	Classification	H-phrases M factor acute M factor chronic	Specific concentration limits ATE	Note
			resp. tract irrit., STOT RE 2			
titan(IV) oxide	13463-67-7 236-675-5 01-2119489379-17 022-006-00-2	2,5 - <5%	Carc. 2	H351 - -		-
trizinc bis(orthophosphate)	7779-90-0 231-944-3 01-2119485044-40 030-011-00-6	0 - <2,5%	Aquatic Acute 1, Aquatic Chronic 1	H400, H410 - -		-
propan-2-ol	67-63-0 200-661-7 01-2119457558-25 603-117-00-0	0 - <2,5%	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3 - narcosis	H225, H319, H336 - -		-
zinc oxide	1314-13-2 215-222-5 01-2119463881-32 030-013-00-7	0 - <2,5%	Aquatic Acute 1, Aquatic Chronic 1	H400, H410 M-acute=1 M-chro=1		-
Epoxy resin	25036-25-3 682-390-8 - -	0 - <2,5%	Skin Irrit. 2, Skin Sens. 1, Eye Irrit. 2	H315, H317, H319 - -		-

Product based on

Mixture of listed substances with non-hazardous additions.

Substance additional information

The content of benzene (EINECS No. 200-753-7) in the individual components is below 0.1% (Note P Annex VI to Directive (EC) No. 1272/2008).

xylene : Contains ethylbenzene CAS 100-41-4

For the complete text of H- / EUH-statements mentioned in this section, see section 16.

TECPO 1K Epoxy- Primer grau_EN

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Get plenty of fresh air and consult a doctor to be on the safe side.

If unconscious, position and transport in the recovery position.

Skin contact

Wash off immediately with soap and water and rinse thoroughly.

Eye contact

Rinse opened eye for several minutes under running water. If symptoms persist consult a doctor if symptoms persist.

Ingestion

Drink plenty of water and get fresh air. Consult a doctor immediately.

4.2. Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3. Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol-resistant foam. Adapt fire extinguishing measures to the surroundings.

5.2. Special hazards arising from the substance or mixture

Formation of toxic gases when heated or in case of fire.

5.3. Advice for firefighters

Special protective equipment for fire-fighters

Put on the breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Put on the breathing apparatus.

Wear protective equipment. Keep unprotected persons away. Keep ignition sources away.



TECPO 1K Epoxy- Primer grau_EN

Version number: 1.0
Issued: 2026-07-11

6.2. Environmental precautions

If the product enters the sewage system/surface water/groundwater, inform the responsible authority.
Do not allow to enter drains/surface water/ground water.

6.3. Methods and material for containment and cleaning up

Use neutralizing agent. Dispose of contaminated material as waste according to section 13. Ensure sufficient ventilation.

6.4. Reference to other sections

See SECTIONS 7+8+13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Preventive handling precautions

Ensure good ventilation/extraction at the workplace.

Notes on fire and explosion protection:

Do not spray on a naked flame or any incandescent material.

Keep ignition sources away - do not smoke.

Have breathing apparatus ready.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and containers:

The official regulations for the storage of pressurized aerosols must be observed.

Storage instructions:

Not required.

Further information on storage conditions:

Keep containers tightly closed.

Storage class according to TRGS 510: 2B Compressed gas packs (aerosol dispensers)

7.3. Specific end use(s)

No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits

Additional information: The lists valid at the time of preparation were used as a basis.



TECPO 1K Epoxy- Primer grau_EN

Version number: 1.0
Issued: 2026-07-11

National occupational exposure limits

Ingredient	CAS No. EC No.	Exposure limit ppm / mg/m ³	Source	Remark	Year
dimethyl ether	115-10-6 204-065-8	1000 / 1900	TRGS 900	8(II); DFG, EU	-
n-butyl acetate	123-86-4 204-658-1	62 / 300	TRGS 900	2(I); AGS, Y	-
Xylene (mixture of isomers)	- 905-588-0	50 / 220	TRGS 900	2(II); DFG, EU, H	-
acetone	67-64-1 200-662-2	500 / 1200	TRGS 900	2(I); AGS, DFG, EU, Y	-
butan-1-ol	71-36-3 200-751-6	100 / 310	TRGS 900	1(I); DFG, Y	-
trizinc bis(orthophosphate)	7779-90-0 231-944-3	- / 0,1	MAK	alveolar-dependent	-
trizinc bis(orthophosphate)	7779-90-0 231-944-3	- / 2	MAK	breathable	-
propan-2-ol	67-63-0 200-661-7	200 / 500	TRGS 900	2(II) ; DFG, Y	-

Biological limit values

Product/Sub- stance name CAS No.	Parameter	Limit value	Test material	Sampling time	Source	Remark	Date
Xylene (mixture of isomers) -	Methylhippuric (toluric) acid (all isomers)	2000 mg/L	Urine	End of expos- ure or end of shift	TRGS 903		
Xylene (mixture of isomers) -	xylene	0 mg/L	Whole blood	End of expos- ure or end of shift	TRGS 903		
acetone 67-64-1	acetone	50 mg/L	Urine	End of expos- ure or end of shift	TRGS 903		
butan-1-ol 71-36-3	Butan-1ol (1- butanol) (after hydrolysis)	2 mg/g cre- atinine	Urine	before the fol- lowing shift			
butan-1-ol 71-36-3	Butan-1ol (1- butanol) (after hydrolysis)	10 mg/g creatinine	Urine	End of expos- ure or end of shift			
propan-2-ol 67-63-0	Acetone.	25 mg/L	Urine	End of expos- ure or end of shift	TRGS 903		

TECPO 1K Epoxy- Primer grau_EN

Product/Sub- stance name CAS No.	Parameter	Limit value	Test material	Sampling time	Source	Remark	Date
propan-2-ol 67-63-0	Acetone.	25 mg/L	Whole blood	End of expos- ure or end of shift	TRGS 903		

8.2. Exposure controls

Appropriate engineering controls

see SECTION 7.

Personal Protective Equipment Symbols



Eye / face protection

Tightly sealed safety goggles

Hand protection

Wear protective gloves.

Glove material: Butyl rubber.

The selection of a suitable glove depends not only on the material but also on other quality features and varies from manufacturer to manufacturer. Since the product is a preparation of several substances, the resistance of glove materials cannot be calculated in advance and must therefore be checked before use.

Penetration time of the glove material:

Butyl rubber gloves with a material thickness of 0.4 mm are resistant to:

Aceton 480 min

Butylacetat 60 min

Ethylacetat 170 min

Xylol 42 min

Gloves made of butyl rubber with a thickness of 0.4 mm are resistant to solvents for 42 - 480 minutes.

As a precautionary measure, we recommend that users and those responsible for occupational safety take a resistance of 42 minutes as a basis. Taking into account the information in chapter 3 of the SDS, it is possible to assume a higher resistance in individual cases.

Respiratory protection

For short-term or low exposure use breathing filter device; for intensive or prolonged exposure use self-contained breathing apparatus.

Filter A2/P3

TECPO 1K Epoxy- Primer grau_EN

Other

General protective and hygiene measures:

Keep away from food, drink and animal feeding stuffs.

Remove soiled, soaked clothing immediately. Wash hands before breaks and at the end of work.

Do not inhale gases/vapors/aerosols. Avoid contact with eyes and skin.

Avoid contact with eyes.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state

Aerosol

Colour

According to product description

Odour

Characteristic.

Odour threshold

Not determined.

Melting point / freezing point

Not determined.

Boiling point or initial boiling point and boiling range

Not applicable as aerosol.

Flammability

Not applicable.

Lower and upper explosion limit

Lower: 1.2% by volume; Lower: 26.2% by volume

Flash point

Not applicable as aerosol.

Auto-ignition temperature

240 °C

Decomposition temperature

Not determined.

pH

Not determined.

Kinematic viscosity

Not determined.

TECPO 1K Epoxy- Primer grau_EN

Viscosity, dynamic

Not determined.

Solubility

No data available

Water solubility

Not or only slightly miscible.

Partition coefficient n-octanol/water

Not determined.

Vapour pressure

4000 hPa

Method

@ 20 °C

Density and/or relative density

0,8 g/cm³

Method

@ 20 °C

Relative density

Not determined.

Relative vapour density

Not determined.

Evaporation Rate

Not applicable.

Explosive properties

Not determined.

Oxidising properties

Not applicable.

VOC %

90,5 %

Particle characteristics

No data available

Information on basic physical and chemical properties

Extremely flammable aerosol. Pressurised container: May burst if heated.

9.2. Other information

No data available

TECPO 1K Epoxy- Primer grau_EN

SECTION 10: Stability and reactivity

10.1. Reactivity

No further relevant information available.

10.2. Chemical stability

No decomposition when used as intended.

10.3. Possibility of hazardous reactions

No dangerous reactions are known.

10.4. Conditions to avoid

No further relevant information available.

10.5. Incompatible materials

No further relevant information available.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Based on available data, the classification criteria are not met.

Acute toxicity

Based on available data, the classification criteria are not met.

Product / Sub- stance name CAS / EC no.	Dose descriptor	Value / Dose	Exposure route	Duration of exposure	Test animals	Method / Guideline
propan-2-ol 67-63-0 / 200- 661-7	LD50	13900 mg/kg	Dermal	-	Rabbit	-
Xylene (mixture of isomers) / 905-588-0	LD50	3523 mg/kg	Oral	-	Rat	-
Xylene (mixture of isomers) / 905-588-0	LD50	2000 mg/kg	Dermal	-	Rabbit	-
Xylene (mixture of isomers) / 905-588-0	LC50	29000 mg/m³	Inhalative	4 hours	Rat	-
acetone	LD50	5800 mg/kg	Oral	-	Rat	-



TECPO 1K Epoxy- Primer grau_EN

Version number: 1.0
Issued: 2026-07-11

Product / Sub- stance name CAS / EC no.	Dose descriptor	Value / Dose	Exposure route	Duration of exposure	Test animals	Method / Guideline
67-64-1 / 200- 662-2						
acetone 67-64-1 / 200- 662-2	LD50	>15800 mg/kg	Dermal	-	Rabbit	-
acetone 67-64-1 / 200- 662-2	LC50	76 mg/l	Inhalative	4 hours	Rat	-
butan-1-ol 71-36-3 / 200- 751-6	LD50	2292 mg/kg	Oral	-	Rat	-
butan-1-ol 71-36-3 / 200- 751-6	LD50	3430 mg/kg	Dermal	-	Rabbit	-
butan-1-ol 71-36-3 / 200- 751-6	LC50	17000 mg/m ³	Inhalative	4 hours	Rat	-
n-butyl acetate 123-86-4 / 204- 658-1	LD50	10800 mg/kg	Oral	-	Rat	OECD 401
n-butyl acetate 123-86-4 / 204- 658-1	LD50	>17600 mg/kg	Dermal	-	Rabbit	-
n-butyl acetate 123-86-4 / 204- 658-1	LC50	21 mg/kg	Inhalative	4 hours	Rat	-
propan-2-ol 67-63-0 / 200- 661-7	LC50	>25 mg/l	Inhalative	6 hours	Rat	-
propan-2-ol 67-63-0 / 200- 661-7	LD50	5840 mg/kg	Oral	-	Rat	-

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

Causes serious eye damage.

Respiratory or skin sensitisation

May cause an allergic skin reaction.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

TECPO 1K Epoxy- Primer grau_EN

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Endocrine disrupting properties

None of the ingredients are included.

SECTION 12: Ecological information

12.1. Toxicity

Acute fish toxicity

Product / Substance name CAS / EC no.	Measurement type	Value / Result	Duration of exposure	Species
propan-2-ol 67-63-0 / 200-661-7	LC50	9640 mg/l	96 hours	Pimephales promelas (Fat-head Minnow)
Xylene (mixture of iso- mers) / 905-588-0	LC50	13,5 mg/l	96 hours	fish
acetone 67-64-1 / 200-662-2	LC50	8300 mg/l	96 hours	fish
butan-1-ol 71-36-3 / 200-751-6	LC50	1376 mg/l	96 hours	fish
dimethyl ether 115-10-6 / 204-065-8	LC50	>4000 mg/l	96 hours	fish

Acute algae toxicity



TECPO 1K Epoxy- Primer grau_EN

Version number: 1.0
Issued: 2026-07-11

Product / Substance name CAS / EC no.	Measurement type	Value / Result	Duration of exposure	Species
acetone 67-64-1 / 200-662-2	EC50	7200 mg/l	96 hours	algae
dimethyl ether 115-10-6 / 204-065-8	EC50	155 mg/l	96 hours	algae

Acute crustacean toxicity

Product / Substance name CAS / EC no.	Measurement type	Value / Result	Duration of exposure	Species
propan-2-ol 67-63-0 / 200-661-7	LC 50	9714 mg/l	24 hours	Daphnia magna
acetone 67-64-1 / 200-662-2	LC50	8450 mg/l	48 hours	water flea
dimethyl ether 115-10-6 / 204-065-8	LC50	>4000 mg/l	48 hours	Daphnia magna
Xylene (mixture of iso- mers) / 905-588-0	EC50	7,4 mg/l	48 hours	Daphnia magna

12.2. Persistence and degradability

No further relevant information available.

12.3. Bioaccumulative potential

No further relevant information available.

12.4. Mobility in soil

Mobility

No further relevant information available.

12.5. Results of PBT and vPvB assessment

This product does not contain any PBT or vPvB substances.

12.6. Endocrine disrupting properties

The product does not contain any substances with endocrine-disrupting properties.

12.7. Other adverse effects

Harmful to fish.

Other

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic life.

TECPO 1K Epoxy- Primer grau_EN

German Water Class

WGK2 - significantly water endangering

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal considerations

Must not be disposed of together with household waste. Do not allow to enter drains.
Disposal in accordance with official regulations.

Packaging

Uncleaned packaging: Disposal in accordance with official regulations.

Waste code	Waste description
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances
15 01 04	metallic packaging
15 01 10*	packaging containing residues of or contaminated by hazardous substances

Please note - an asterisk (*) next to a code denotes that it is HAZARDOUS WASTE.

SECTION 14: Transport information

14.1. UN number

1950

14.2. UN proper shipping name

ADR / RID / ADN proper shipping name

AEROSOLS, flammable

IMDG proper shipping name

AEROSOLS

TECPO 1K Epoxy- Primer grau_EN

14.3. Transport hazard class(es)

Label

ADR/RID/ADN



2.1

IMDG



2.1

ADR / RID Class

2

Tunnel restriction code: D

Transportation category: 2

ADR / RID Classification code

5F

IMDG Class

2

14.4. Packing group

ADR: -

IMDG: -

14.5. Environmental hazards

Not applicable.

IMDG Marine Pollutant

Not applicable.

14.6. Special precautions for user

Caution: Flammable gases.

IMDG EmS

F-D, S-U

14.7. Maritime transport in bulk according to IMO instruments

Not applicable.



TECPO 1K Epoxy- Primer grau_EN

Version number: 1.0
Issued: 2026-07-11

Other

Additional information ADR-RID

Limited quantity: 1 L
Exempted quantity E0

Additional information IMDG

Limited quantity: 1 L
Exempted quantity E0

TECPO 1K Epoxy- Primer grau_EN

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Directive 2012/18/EU - Named dangerous substances - ANNEX I

None of the ingredients are included.

Information on the SEVESO III Directive 2012/18/EU:

P3a FLAMMABLE AEROSOLE

REGULATION (EU) 2019/1021 on persistent organic pollutants (POPs)

None of the ingredients are included.

The product is subject to the following restrictions according to Annex XVII, Regulation (EC) 1907/2006 (REACH): 3

Directive 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment - Annex II

None of the ingredients are included.

Regulation (EC) No 273/2004 on drug precursors

67-64-1 Acetone

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug substitutes

67-64-1 Acetone

Marketing and use of explosives precursors (Regulation (EU) 2019/1148): This product is regulated by Regulation (EU) 2019/1148: All suspicious transactions and the loss and theft of significant quantities must be reported to the relevant national contact point.

67-64-1 Acetone



TECPO 1K Epoxy- Primer grau_EN

Version number: 1.0
Issued: 2026-07-11

National regulations

Technical guidance on air:

Class Proportion in % No ingredients of classes I - III TA Luft No. 5.2.7.1

Water hazard class (WGK): 2, significantly hazardous to water.

Storage class: 2B Compressed gas packs (aerosol dispensers)

Substances of Very High Concern (SVHC) according to REACH, Article 57:

None of the ingredients are included.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

TECPO 1K Epoxy- Primer grau_EN

SECTION 16: Other information

Abbreviations

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road
AGW - Occupational Exposure Limit (Arbeitsplatzgrenzwert)
ATE - Acute Toxicity Estimate
AwSV - Ordinance on Installations for Handling Substances Hazardous to Water
C&L - Einstufung und Kennzeichnung
CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
CMR - Carcinogen, Mutagen, or Reproductive Toxicant
CSR - Chemical Safety Report
DNEL - Derived No Effect Level
ECHA - European Chemicals Agency
GefStoffV - Hazardous Substances Ordinance (Gefahrstoffverordnung)
GHS - Globally Harmonized System
IMDG - International Maritime Dangerous Goods
International Air Transport Association
IUCLID - International Uniform Chemical Information Database
Kow - octanol-water partition coefficient
LC50 - Lethal Concentration to 50 % of a test population
LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose)
LGK - Storage Class (Lagerklasse)
OEL - Occupational Exposure Lim
PBT - Persistent, Bioaccumulative and Toxic substance
PNEC - Predicted No Effect Concentration(s)
REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID - Regulations concerning the International Carriage of Dangerous Goods by Rail
SCBA - Self-Contained Breathing Apparatus
STOT - Specific Target Organ Toxicity
SVHC - Substances of Very High Concern
TRGS - Technische Regeln für Gefahrstoffe
UFI - Unique Formula Identifier
vPvB - Very Persistent and Very Bioaccumulative
WGK - Water Hazard Class (Wassergefährdungsklasse)

TECPO 1K Epoxy- Primer grau_EN

Phrase meaning

Aerosol 1 - Aerosol, Hazard category 1
Skin Irrit. 2 - Skin irritation, hazard category 2
Skin Sens. 1 - Skin sensitisation, hazard category 1
Eye Dam. 1 - Serious eye damage, hazard category 1
STOT SE 3 - narcosis - Specific Target Organ Toxicity — Single exposure, hazard category 3 - narcosis
Aquatic Chronic 3 - Hazardous to the aquatic environment — Chronic hazard category 3
Flam. Gas 1 - Flammable gases, hazard category 1
Press. Gas - Liquefied gas - Gases under pressure, Liquefied gas
Flam. Liq. 3 - Flammable liquids, hazard category 3
Asp. Tox. 1 - Aspiration hazard, hazard category 1
Acute Tox. 4 - dermal - Acute toxicity, dermal, hazard category 4
Eye Irrit. 2 - Eye irritation, hazard category 2
Acute Tox. 4 - inhalation - Acute toxicity, inhalation, hazard category 4
STOT SE 3 - resp. tract irrit. - Specific Target Organ Toxicity — Single exposure, hazard category 3 - respiratory tract irritation
STOT RE 2 - Specific Target Organ Toxicity — Repeated exposure, hazard category 2
Flam. Liq. 2 - Flammable liquids, hazard category 2
Acute Tox. 4 - oral - Acute toxicity, oral, hazard category 4
Carc. 2 - Carcinogenicity, hazard category 2
Aquatic Acute 1 - Hazardous to the aquatic environment — Acute hazard category 1
Aquatic Chronic 1 - Hazardous to the aquatic environment — Chronic hazard category 1
H220 Extremely flammable gas.
H222 Extremely flammable aerosol.
H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H229 Pressurised container: May burst if heated
H280 Contains gas under pressure; may explode if heated.
H302 Harmful if swallowed.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H351 Suspected of causing cancer.
H373 May cause damage to organs through prolonged or repeated exposure
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.
EUH066 Repeated exposure may cause skin dryness or cracking.
EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.



TECPO 1K Epoxy- Primer grau_EN

Version number: 1.0
Issued: 2026-07-11

Other

Additional information

The information is based on our current state of knowledge, but does not constitute a guarantee of product properties and does not establish a contractual legal relationship. The recipient of our products is responsible for observing existing laws and regulations. The information in this safety data sheet corresponds to the best of our knowledge at the time of printing. The information is intended to provide you with guidelines for the safe handling of the product mentioned in this safety data sheet during storage, processing, transportation and disposal. The information is not transferable to other products. If the product is mixed, blended or processed with other materials processed or subjected to processing, the information in this safety data sheet cannot be transferred to the new material produced in this way, unless expressly stated otherwise.

Manufacturer's notes

The data of the relevant components were taken from the latest safety data sheet of the upstream supplier.