TECPO 1K Teppich-/Matten-Farbspray Schwarz_EN

Version number: 1.0
Issued: 2025-04-23

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name
TECPO 1K Teppich-/Matten-Farbspray Schwarz_EN

Article No.
300862

UFI code
JC7V-CU8N-F00J-HQVW

1.2. Relevant identified uses of the substance or mixture and uses advised against

Product type
PC9a - Coatings and paints, thinners, paint removers.

Relevant identified uses
Paint.

Application:
SU21 - Consumer uses: Private households (= general public = consumers).
SU22 - Professional uses: Public domain (administration, education, entertainment, services, crafts-men).
Process category:
PROC7 - Industrial spraying.
PROC11 - Non industrial spraying.

Not suitable for use in
No further relevant information available.

1.3. Details of the supplier of the safety data sheet

SDS created by
Gefahrgutberatung Florian Herber, Erbigsweg 12, 36137 Großenlüder
Telefon: 0163 / 8408334
E-Mail: kontakt@gefahrgut-herber.de
www.gefahrgut-herber.de

TECPO 1K Teppich-/Matten-Farbspray Schwarz_EN

Supplier
TECPO GmbH

Address
Dreherstraße 16-20

42899 Remscheid
Germany

Telephone
+49 2191 951 3305

Email
info@tecpo.de

Fax
+49 2191 951 33044

Web site
www.tecpo.de

1.4. Emergency telephone number

Poison center/Additional emergency number
+49 (0) 89 19240 - Poison Emergency Call Munich

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Classification
Aerosol, Hazard category 1
Eye irritation, hazard category 2
Specific Target Organ Toxicity — Single exposure, hazard category 3 - narcosis

Hazard statements
H222, H229, H319, H336

Description
The product is classified and labeled according to the CLP regulation.

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008

Hazard pictograms

Signal word

Danger

Hazard statements

H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

Supplemental hazard statements

EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P260 Do not breathe aerosol.
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
P501 Dispose of contents/container to dispose of in accordance with local / regional / national / international regulations.

More information

Hazard-determining components of labeling:
acetone
2-Methoxy-1-methyl ethyl acetate
Ethyl acetate
n-butyl acetate

2.3. Other hazards

Formation of explosive mixtures possible without adequate ventilation.

Other

This product does not contain any PBT or vPvB substances.

Endocrine disrupting properties:
78-93-3 butanone
list II

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical name	CAS No. EC No. REACH No. Index No.	Concentration	Classification	H-phrase M factor acute M factor chronic	Note
acetone	67-64-1 200-662-2 01-2119471330-49 606-001-00-8	25 - <50%	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3 - narcosis	H225, H319, H336, EUH066 - -	-
dimethyl ether	115-10-6 204-065-8 01-2119472128-37 603-019-00-8	25 - <50%	Flam. Gas 1, Press. Gas - Liquefied gas	H220, H280 - -	-
propane	74-98-6 200-827-9 01-2119486944-21 601-003-00-5	5 - <10%	Flam. Gas 1A, Press. Gas - Liquefied gas	H220, H280 - -	-
2-methoxy-1-methylethyl acetate	108-65-6 203-603-9 01-2119475791-29 607-195-00-7	5 - <10%	Flam. Liq. 3, STOT SE 3 - narcosis	H226, H336 - -	-
ethyl acetate	141-78-6 205-500-4 01-2119475103-46 607-022-00-5	5 - <10%	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3 - narcosis	H225, H319, H336, EUH066 - -	-
isobutane (containing < 0,1 % butadiene (203-450-8))	75-28-5 200-857-2 01-2119485395-27 601-004-00-0	2,5 - <5%	Flam. Gas 1A, Press. Gas - Compressed gas	H220, H280 - -	-
butane (containing < 0,1 % butadiene (203-450-8))	106-97-8 203-448-7 01-2119474691-32 601-004-01-8	2,5 - <5%	Flam. Gas 1A, Press. Gas	H220, H280 - -	-

Chemical name	CAS No. EC No. REACH No. Index No.	Concentration	Classification	H-phrase M factor acute M factor chronic	Note
n-butyl acetate	123-86-4 204-658-1 01-2119485493-29 607-025-00-1	2,5 - <5%	Flam. Liq. 3, STOT SE 3 - narcosis	H226, H336, EUH066 - -	-
butanone	78-93-3 201-159-0 01-2119457290-43 606-002-00-3	0 - <2,5%	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3 - narcosis	H225, H319, H336, EUH066 - -	-
cellulose nitrate	9004-70-0 - - -	0 - <2,5%	Expl. 1.1	H201 - -	CLP Note T
butan-1-ol	71-36-3 200-751-6 01-2119484630-38 603-004-00-6	0 - <2,5%	Flam. Liq. 3, Acute Tox. 4 - oral, Skin Irrit. 2, Eye Dam. 1, STOT SE 3 - resp. tract irrit., STOT SE 3 - narcosis	H226, H302, H315, H318, H335, H336 - -	-
Xylene	- 905-588-0 01-2119488216-32 601-022-00-9	0 - <2,5%	Flam. Liq. 3, Asp. Tox. 1, Acute Tox. 4 - dermal, Skin Irrit. 2, Eye Irrit. 2, Acute Tox. 4 - inhalation, STOT SE 3 - resp. tract irrit., STOT RE 2	H226, H304, H312, H315, H319, H332, H335, H373 - -	-

Product based on
Mixture of listed substances with non-hazardous additions.

Substance additional information
CAS 9004-70-0: CLP-Note T

For the complete text of H- / EUH-statements mentioned in this section, see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Supply fresh air, consult a doctor in case of complaints.

Skin contact

In general, the product is not irritating to the skin.

Eye contact

Rinse opened eye for several minutes under running water. If symptoms persist consult a doctor if symptoms persist.

Ingestion

Drink plenty of water and get fresh air. Consult a doctor immediately.

4.2. Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3. Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Adapt fire extinguishing measures to the surroundings.

5.2. Special hazards arising from the substance or mixture

Formation of toxic gases when heated or in case of fire.

5.3. Advice for firefighters

Special protective equipment for fire-fighters

Put on the breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation.
Put on the breathing apparatus.
Wear protective equipment. Keep unprotected persons away. Keep ignition sources away.

6.2. Environmental precautions
Do not allow to enter drains/surface water/ground water.

6.3. Methods and material for containment and cleaning up
Dispose of contaminated material as waste according to section 13. Ensure sufficient ventilation.

6.4. Reference to other sections
See SECTIONS 7+8+13

SECTION 7: Handling and storage

7.1. Precautions for safe handling
Preventive handling precautions
Ensure good ventilation/extraction at the workplace.

Notes on fire and explosion protection:
Do not spray on a naked flame or any incandescent material.
Keep ignition sources away - do not smoke.
Have breathing apparatus ready.

7.2. Conditions for safe storage, including any incompatibilities
Requirements for storage rooms and containers:
The official regulations for the storage of pressurized aerosols must be observed.

Storage instructions:
Not required.

Further information on storage conditions:
Keep containers tightly closed.

Storage class according to TRGS 510: 2B Compressed gas packs (aerosol dispensers)

7.3. Specific end use(s)
No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters
Exposure limits
Additional information: The lists valid at the time of preparation were used as a basis.

National occupational exposure limits

Ingredient	CAS No. EC No.	Exposure limit ppm / mg/m³	Source	Remark	Year
isobutane (containing < 0,1 % butadiene (203-450-8))	75-28-5 200-857-2	1000 / 2400 /	AGW	4(II); DFG	-
butane (containing < 0,1 % butadiene (203-450-8))	106-97-8 203-448-7	1000 / 2400 /	AGW	4(II); DFG	2006
propane	74-98-6 200-827-9	1000 / 1800 /	AGW	4 (II)	-
acetone	67-64-1 200-662-2	500 / 1200 /	AGW	AGS, DFG, EU, Y	-
dimethyl ether	115-10-6 204-065-8	1000 / 1900 /	TRGS 900	8(II); DFG, EU	-
2-methoxy-1-methylethyl acetate	108-65-6 203-603-9	50 / 270 /	TRGS 900	I(I); DFG, EU, Y	-
ethyl acetate	141-78-6 205-500-4	200 / 730 /	AGW	2(I); DFG, EU, Y	-
butanone	78-93-3 201-159-0	200 / 600 /	AGW	1(1);DFG, EU, H, Y	-
butan-1-ol	71-36-3 200-751-6	100 / 310 /	AGW	1(I); DFG, Y	-
n-butyl acetate	123-86-4 204-658-1	62 / 300 /	AGW	2(I); AGS, Y	-
Xylene	- 905-588-0	50 / 220 /	AGW	2(II); DFG, EU, H	-

Biological limit values

Product/Substance name CAS No.	Parameter	Limit value	Test material	## missing phrase ##	Source	Remark	Date
acetone 67-64-1	acetone	80 mg/l	Urine	end of exposure or end of shift			
butanone 78-93-3	2- butanone	2 mg/l	Urine	end of exposure or end of shift			
butan-1-ol 71-36-3	Butan-1ol (1-butanol) (after hydrolysis)	2 mg/g creatinine	Urine	before the following shift			

Product/Substance name CAS No.	Parameter	Limit value	Test material	## missing phrase ##	Source	Remark	Date
butan-1-ol 71-36-3	Butan-1ol (1-butanol) (after hydrolysis)	10 mg/g creatinine	Urine	end of exposure or end of shift			
Xylene -	Xylene.	2 mg/l	Whole blood	end of exposure or end of shift			
Xylene -	Methylhippuric (toluric) acid (all isomers)	2000 mg/l	Urine	end of exposure or end of shift			

8.2. Exposure controls

Appropriate engineering controls

see SECTION 7.

Personal Protective Equipment Symbols

Eye / face protection

Tightly sealed safety goggles

Hand protection

Wear protective gloves.
Glove material: Butyl rubber.
The selection of a suitable glove depends not only on the material, but also on other quality features and varies from manufacturer to manufacturer.

Penetration time of the glove material:
Butyl rubber gloves with a material thickness of 0.4 mm are resistant to:
Aceton 480 min
Butylacetat 60 min
Ethylacetat 170 min
Xylol 42 min
Gloves made of butyl rubber with a thickness of 0.4 mm are resistant to solvents for 42 - 480 minutes. As a precautionary measure, we recommend that users and those responsible for occupational safety take a resistance of 42 minutes as a basis. Taking into account the information in chapter 3 of the SDS, it is possible to assume a higher resistance in individual cases.

Respiratory protection
For short-term or low exposure use breathing filter device; for intensive or prolonged exposure use self-contained breathing apparatus.
Filter A2/P3

Other

General protective and hygiene measures:
Keep away from food, drink and animal feeding stuffs.
Remove soiled, soaked clothing immediately. Wash hands before breaks and at the end of work.
Do not inhale gases/vapors/aerosols.
Avoid contact with eyes. Avoid contact with eyes and skin.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state
Aerosol

Colour
Black.

Odour
by solvent

Odour threshold
Not determined.

Melting point / freezing point
Not determined.

Boiling point or initial boiling point and boiling range
Not applicable as aerosol.

Flammability
Not applicable.

Lower and upper explosion limit
Lower: 2.6 % by volume; Upper: 26.2 % by volume

Flash point
Not applicable as aerosol.

Auto-ignition temperature
240 °C

Decomposition temperature
Not determined.

pH
Mixture is insoluble in water.

Kinematic viscosity
Not determined.

Viscosity, dynamic
Not determined.

Solubility
No data available

Water solubility
Not or only slightly miscible.

Partition coefficient n-octanol/water
Not determined.

Vapour pressure
4000 hPa
Method
@ 20 °C

Density and/or relative density
0,7 g/cm³
Method
@ 20 °C

Relative density
Not determined.

Relative vapour density
Not determined.

Evaporation Rate
Not applicable.

Explosive properties
Not determined.

Oxidising properties
Not determined.

VOC %
94,46 %

Particle characteristics
No data available

Information on basic physical and chemical properties
Extremely flammable aerosol. Pressurised container: May burst if heated.

9.2. Other information
No data available

SECTION 10: Stability and reactivity

10.1. Reactivity
No further relevant information available.

10.2. Chemical stability
No decomposition when used as intended.

10.3. Possibility of hazardous reactions
No dangerous reactions are known.

10.4. Conditions to avoid
No further relevant information available.

10.5. Incompatible materials
No further relevant information available.

10.6. Hazardous decomposition products
No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008
Acute toxicity
Based on available data, the classification criteria are not met.

Product / Substance name CAS / EC no.	Dose descriptor	Value / Dose	Exposure route	Duration of exposure	Test animals	Method / Guideline
acetone 67-64-1 / 200-	LD50	5800 mg/kg	Oral	-	Rat	-

Product / Substance name CAS / EC no.	Dose descriptor	Value / Dose	Exposure route	Duration of exposure	Test animals	Method / Guideline
662-2						
acetone 67-64-1 / 200-662-2	LD50	>15800 mg/kg	Dermal	-	Rabbit	-
acetone 67-64-1 / 200-662-2	LC50	76 mg/l	Inhalative	4 hours	Rat	-
acetone 67-64-1 / 200-662-2	LC50	5540 mg/l	Inhalative	96 hours	Onchorhynchus mykiss (Rainbow trout)	-
2-methoxy-1-methylethyl acetate 108-65-6 / 203-603-9	LD50	8530 mg/kg	Oral	-	Rat	-
2-methoxy-1-methylethyl acetate 108-65-6 / 203-603-9	LD50	>5000 mg/kg	Dermal	-	Rabbit	-
2-methoxy-1-methylethyl acetate 108-65-6 / 203-603-9	LC50	>10000 mg/m³	Inhalative	4 hours	Rat	-
ethyl acetate 141-78-6 / 205-500-4	LD50	>18000 mg/kg	Oral	-	Rabbit	-
ethyl acetate 141-78-6 / 205-500-4	LD50	5620 mg/kg	Dermal	-	Rat	-
ethyl acetate 141-78-6 / 205-500-4	LC50	1600 mg/m³	Inhalative	4 hours	Rat	-
butanone 78-93-3 / 201-159-0	LD50	> 2193 mg/kg	Oral	-	Rat	-
butanone 78-93-3 / 201-159-0	LD50	> 5000 mg/kg	Dermal	-	Rabbit	-
butanone	LC50	34 mg/m³	Inhalative	4 hours	Rat	-

Product / Substance name CAS / EC no.	Dose descriptor	Value / Dose	Exposure route	Duration of exposure	Test animals	Method / Guideline
78-93-3 / 201-159-0						
Xylene / 905-588-0	LD50	3523 mg/kg	Oral	-	Rat	-
Xylene / 905-588-0	LD50	2000 mg/kg	Dermal	-	Rabbit	-
Xylene / 905-588-0	LC50	29000 mg/m³	Inhalative	4 hours	Rat	-
butan-1-ol 71-36-3 / 200-751-6	LD50	2292 mg/kg	Oral	-	Rat	-
butan-1-ol 71-36-3 / 200-751-6	LD50	3430 mg/kg	Dermal	-	Rabbit	-
butan-1-ol 71-36-3 / 200-751-6	LC50	17000 mg/m³	Inhalative	4 hours	Rat	-
n-butyl acetate 123-86-4 / 204-658-1	LD50	10800 mg/kg	Oral	-	Rat	OECD 401
n-butyl acetate 123-86-4 / 204-658-1	LD50	>17600 mg/kg	Dermal	-	Rabbit	-
n-butyl acetate 123-86-4 / 204-658-1	LC50	21 mg/kg	Inhalative	4 hours	Rat	-

Skin corrosion/irritation
Based on available data, the classification criteria are not met. No irritant effect.

Serious eye damage/irritation
Causes serious eye irritation.

Respiratory or skin sensitisation
Based on available data, the classification criteria are not met. No sensitizing effect known.

Germ cell mutagenicity
Based on available data, the classification criteria are not met.

Carcinogenicity
Based on available data, the classification criteria are not met.

Reproductive toxicity
Based on available data, the classification criteria are not met.

STOT-single exposure
May cause drowsiness or dizziness.

STOT-repeated exposure
Based on available data, the classification criteria are not met.

Aspiration hazard
Based on available data, the classification criteria are not met.

11.2. Information on other hazards
Endocrine disrupting properties
78-93-3 butanone
list II

SECTION 12: Ecological information

12.1. Toxicity
Acute fish toxicity

Product / Substance name CAS / EC no.	Measurement type	Value / Result	Duration of exposure	Species
acetone 67-64-1 / 200-662-2	LC50	8300 mg/l	96 hours	fish
dimethyl ether 115-10-6 / 204-065-8	LC50	>4000 mg/l	96 hours	fish
2-methoxy-1-methylethyl acetate 108-65-6 / 203-603-9	LC50	100-180 mg/l	96 hours	Onchorhynchus mykiss (Rainbow trout)
butanone 78-93-3 / 201-159-0	LC50	2990 mg/l	96 hours	fish
butan-1-ol 71-36-3 / 200-751-6	LC50	1376 mg/l	96 hours	fish
Xylene / 905-588-0	LC50	13,5 mg/l	96 hours	fish

Acute algae toxicity

Product / Substance name CAS / EC no.	Measurement type	Value / Result	Duration of exposure	Species
acetone 67-64-1 / 200-662-2	EC50	7200 mg/l	96 hours	algae
dimethyl ether 115-10-6 / 204-065-8	EC50	155 mg/l	96 hours	algae
butanone 78-93-3 / 201-159-0	LC50	1972 mg/l	72 hours	Pseudokirchneriella subcapitata

Acute crustacean toxicity

Product / Substance name CAS / EC no.	Measurement type	Value / Result	Duration of exposure	Species
acetone 67-64-1 / 200-662-2	LC50	8450 mg/l	48 hours	water flea
dimethyl ether 115-10-6 / 204-065-8	LC50	>4000 mg/l	48 hours	Daphnia magna
2-methoxy-1-methylethyl acetate 108-65-6 / 203-603-9	EC50	>500 mg/l	48 hours	Daphnia magna
butanone 78-93-3 / 201-159-0	LC50	308 mg/l	48 hours	Daphnia magna
Xylene / 905-588-0	EC50	7,4 mg/l	48 hours	Daphnia magna

12.2. Persistence and degradability
No further relevant information available.

12.3. Bioaccumulative potential
No further relevant information available.

Product / Substance name CAS / EC no.	LogKow / LogPow
propane 74-98-6 / 200-827-9	1,09
propane 74-98-6 / 200-827-9	1,09

12.4. Mobility in soil

Mobility

No further relevant information available.

12.5. Results of PBT and vPvB assessment

Not Classified as PBT/vPvB by current EU criteria.

12.6. Endocrine disrupting properties

For information on endocrine disrupting properties see section 11.

12.7. Other adverse effects

No data available

Other

Do not allow undiluted product or large quantities of it to enter groundwater, watercourses or drains.
into the sewage system.

German Water Class

WGK1 - slightly water endangering

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal considerations

Must not be disposed of together with household waste. Do not allow to enter drains.
Disposal in accordance with official regulations.

Packaging

Uncleaned packaging: Disposal in accordance with official regulations.

Waste code	Waste description
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances
15 01 04	metallic packaging

Please note - an asterisk (*) next to a code denotes that it is HAZARDOUS WASTE.

SECTION 14: Transport information

14.1. UN number

1950

14.2. UN proper shipping name

ADR / RID / ADN proper shipping name

AEROSOLS, flammable

IMDG proper shipping name

AEROSOLS

14.3. Transport hazard class(es)

Label

ADR/RID/ADN

2.1

IMDG

2.1

ADR / RID Class

2
Tunnel restriction code: D
Transportation category: 2

ADR / RID Classification code

5F

IMDG Class

2

14.4. Packing group

ADR: -
IMDG: -

14.5. Environmental hazards

Not applicable.

IMDG Marine Pollutant

Not applicable.

14.6. Special precautions for user

Caution: Flammable gases.

IMDG EmS
F-D, S-U

14.7. Maritime transport in bulk according to IMO instruments
Not applicable.

Other
Additional information ADR-RID
Limited quantity: 1 L

Additional information IMDG
Limited quantity: 1 L

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
EU regulations
Information on the SEVESO III Directive 2012/18/EU:
Named dangerous substances - ANNEX I None of the ingredients are included.
P3a FLAMMABLE AEROSOLE

Annex XVII (REACH): The product is subject to the following restrictions according to Annex XVII, Regulation (EC) 1907/2006 (REACH): 3

Directive 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment - Annex II
None of the ingredients are included.

Regulation (EC) No 273/2004 on drug precursors
67-64-1 Acetone
78-93-3 butanone

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug substitutes 67-64-1 Acetone
78-93-3 butanone

National regulations
Technical guidance on air:
Class Proportion in % No ingredients of classes I - III TA Luft No. 5.2.7.1

Water hazard class (WGK): 1, slightly hazardous to water.

Storage class: 2B Compressed gas packs (aerosol dispensers)

Substances of Very High Concern (SVHC) according to REACH, Article 57:
None of the ingredients are included.

15.2. Chemical safety assessment
No chemical safety assessment has been carried out.

SECTION 16: Other information

Abbreviations

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road
AGW - Occupational Exposure Limit (Arbeitsplatzgrenzwert)
ATE - Acute Toxicity Estimate
AwSV - Ordinance on Installations for Handling Substances Hazardous to Water
C&L - Einstufung und Kennzeichnung
CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
CMR - Carcinogen, Mutagen, or Reproductive Toxicant
CSR - Chemical Safety Report
DNEL - Derived No Effect Level
ECHA - European Chemicals Agency
GefStoffV - Hazardous Substances Ordinance (Gefahrstoffverordnung)
GHS - Globally Harmonized System
IMDG - International Maritime Dangerous Goods
International Air Transport Association
IUCLID - International Uniform Chemical Information Database
Kow - octanol-water partition coefficient
LC50 - Lethal Concentration to 50 % of a test population
LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose)
LGK - Storage Class (Lagerklasse)
OEL - Occupational Exposure Lim
PBT - Persistent, Bioaccumulative and Toxic substance
PNEC - Predicted No Effect Concentration(s)
REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID - Regulations concerning the International Carriage of Dangerous Goods by Rail
SCBA - Self-Contained Breathing Apparatus
STOT - Specific Target Organ Toxicity
SVHC - Substances of Very High Concern
TRGS - Technische Regeln für Gefahrstoffe
UFI - Unique Formula Identifier
vPvB - Very Persistent and Very Bioaccumulative
WGK - Water Hazard Class (Wassergefährdungsklasse)

Phrase meaning

Aerosol 1 - Aerosol, Hazard category 1
Eye Irrit. 2 - Eye irritation, hazard category 2
STOT SE 3 - narcosis - Specific Target Organ Toxicity — Single exposure, hazard category 3 - narcosis
Flam. Gas 1A - Flammable gases, hazard category 1A
Press. Gas - Compressed gas - Gases under pressure, Compressed gas
Press. Gas - Gases under pressure
Press. Gas - Liquefied gas - Gases under pressure, Liquefied gas
Flam. Liq. 2 - Flammable liquids, hazard category 2
Flam. Gas 1 - Flammable gases, hazard category 1
Flam. Liq. 3 - Flammable liquids, hazard category 3
Expl. 1.1 - Explosives of Divisions 1.1
Acute Tox. 4 - oral - Acute toxicity, oral, hazard category 4
Skin Irrit. 2 - Skin irritation, hazard category 2
Eye Dam. 1 - Serious eye damage, hazard category 1
STOT SE 3 - resp. tract irrit. - Specific Target Organ Toxicity — Single exposure, hazard category 3 - respiratory tract irritation
Asp. Tox. 1 - Aspiration hazard, hazard category 1
Acute Tox. 4 - dermal - Acute toxicity, dermal, hazard category 4
Acute Tox. 4 - inhalation - Acute toxicity, inhalation, hazard category 4
STOT RE 2 - Specific Target Organ Toxicity — Repeated exposure, hazard category 2
H201 Explosive; mass explosion hazard.
H220 Extremely flammable gas.
H222 Extremely flammable aerosol.
H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H229 Pressurised container: May burst if heated.
H280 Contains gas under pressure; may explode if heated.
H302 Harmful if swallowed.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H373 May cause damage to organs through prolonged or repeated exposure .
EUH066 Repeated exposure may cause skin dryness or cracking.

TECPO 1K Teppich-/Matten-Farbspray Schwarz_EN

Other

Additional information

The information is based on our current state of knowledge, but does not constitute a guarantee of product properties and does not establish a contractual legal relationship. The recipient of our products is responsible for observing existing laws and regulations. The information in this safety data sheet corresponds to the best of our knowledge at the time of printing. The information is intended to provide you with guidelines for the safe handling of the product mentioned in this safety data sheet during storage, processing, transportation and disposal. The information is not transferable to other products. If the product is mixed, blended or processed with other materials
processed or subjected to processing, the information in this safety data sheet cannot be transferred to the new material produced in this way, unless expressly stated otherwise.

Manufacturer's notes

The data of the relevant components were taken from the latest safety data sheet of the upstream supplier.